


Pincas de dépannage - Notfallspannzangen - Emergency collets



Type	Art.	A	B	C	D	E	F	G	α	Fig.
W12 10) 80-2	80-52200	12	16	45.6	1.5	-	-	\emptyset 11.75x1.25 ∇ 45°/5°	15 °	1
	80-50315 14)	12	16	45.6	1.5	-	-	\emptyset 11.75x1.25 ∇ 45°/5°	15 °	1
W20 10) 80-4	80-50300	20	26.3	73	2	-	-	\emptyset 19.7x1.666 ∇ 45°/5°	15 °	1
	80-50314 14)	20	26.3	73	2	-	-	\emptyset 19.7x1.666 ∇ 45°/5°	15 °	1
	80-52365	20	26.3	105.6	6	47	35	\emptyset 19.7x1.666 ∇ 45°/5°	15 °	2
W25 10) 80-5	80-50294	25	33.7	97.6	2	-	-	\emptyset 24.7x1.693 ∇ 45°/5°	15 °	1
	80-50344 14)	25	33.7	97.6	2	-	-	\emptyset 24.7x1.693 ∇ 45°/5°	15 °	1
	80-53004	25	33.7	129	6	47	35	\emptyset 24.7x1.693 ∇ 45°/5°	15 °	2
W31.75 10) 80-842	80-52531	31.75	37.4	87	2	-	-	\emptyset 31.4x1.27 ∇ 60°	10°3'	1
	80-53000 14) & 26)	31.75	37.4	87	2	-	-	\emptyset 31.4x1.27 ∇ 60°	10°3'	1
B6 10) 72-128	72-53005	6	10.5	31.3	1	-	-	\emptyset 5x0.706 ∇ 55°	20°	1
B8 10) 72-137	72-53000	8	13	35.5	1.2	-	-	\emptyset 6.82x0.625 ∇ 55°	20°	1
B32 10) 72-65	72-50615	32	40	106	2	-	-	\emptyset 29.7x1.693 ∇ 45°/5°	15 °	1
	72-52525	32	40	137	6	60	35	\emptyset 29.7x1.693 ∇ 45°/5°	15 °	2
	72-52290 14)	32	40	106	2	-	-	\emptyset 29.7x1.693 ∇ 45°/5°	15 °	1
B45 10) 72-199	72-53001	45	53	115	3	-	-	M42x1.5	15 °	1

10) Article de base
Basisartikel
Basic item

14) Exécution en laiton
Ausführung in Messing
Made from brass material

26) Sur demande
Auf Anfrage
On request