

Pinces - Spannzangen - Collets



avec cône adapté pour la haute vitesse  
 mit flachem Konus für hohe Drehzahlen  
 with special taper for high-speed cutting

qualité UP      serre le diamètre nominal  
 Qualität UP      spannt den Nenndurchmesser  
 quality UP      clamps the nominal diameter



| Type | Art.     | D1    | D2    | D3           | L1   | L2  |
|------|----------|-------|-------|--------------|------|-----|
| D6   | 74-6000  | 6.1   | 5.1   | 0.50...3.17  | 13   | 2.6 |
| D8   | 74-8000  | 8.13  | 6.85  | 0.50...5.00  | 16.5 | 2.8 |
| D10  | 74-10000 | 10.14 | 8.25  | 0.50...6.00  | 20   | 3   |
| D12  | 74-12000 | 12.65 | 9.35  | 0.50...7.00  | 24   | 3.2 |
| D14  | 74-14000 | 14.15 | 11.55 | 0.50...9.00  | 25   | 3.6 |
| D16  | 74-16000 | 16.65 | 12.9  | 0.50...10.00 | 28.5 | 4.2 |
| D20  | 74-20000 | 20.18 | 15.9  | 0.50...12.70 | 32   | 4.6 |
| D24  | 74-24000 | 24.18 | 19.4  | 0.50...16.00 | 35   | 5   |
| D29  | 74-29000 | 29.18 | 23.9  | 1.00...20.00 | 40   | 5.4 |

Alésages standards selon liste de prix. Autres alésages sur demande.  
 Standardbohrungen gemäss Preisliste. Andere Bohrungen auf Anfrage.  
 Standard bores according to price list. Other bores on request.