

**Pinces poussées - Druckspannzangen - Dead length collets**



| Type | Art.                          | A  | B  | C  | E  | F  | G        | α   | D min-max                                       |          |          | Fig. |
|------|-------------------------------|----|----|----|----|----|----------|-----|---|----------|----------|------|
|      |                               |    |    |    |    |    |          |     | ○   | □        | ⬡        |      |
| F13  | <b>76-357</b>                 | 13 | 19 | 64 | 6  | 13 | -        | 16° | 0.3-10.0  | 1.0-7.0  | 1.0-8.0  | 1    |
|      | <b>76-93019</b><br>10) 76-357 | 13 | 19 | 66 | 8  | 13 | M11x0.75 | 16° | 0.3-10.0<br>lisse-glatt-smooth                  |          |          | 4    |
|      | <b>76-2014</b><br>10) 76-357  | 13 | 19 | 70 | 12 | 13 | M11x0.75 | 16° | 0.3-8.0   | 1.0-5.7  | 1.0-7.0  | 3    |
| F14  | <b>76-98</b>                  | 14 | 18 | 46 | 4  | 14 | -        | 13° | 0.3-11.2  | 1.0-8.0  | 1.0-9.7  | 1    |
| F15  | <b>76-358</b>                 | 15 | 22 | 47 | 5  | 15 | -        | 20° | 0.3-11.11                                       | 1.0-7.54 | 1.0-9.52 | 1    |
|      | <b>76-580</b>                 | 15 | 21 | 64 | 6  | 15 | -        | 16° | 0.3-12.7  | 1.0-9.0  | 1.0-11.0 | 1    |
|      | <b>76-2022</b><br>10) 76-580  | 15 | 21 | 71 | 13 | 15 | -        | 16° | 0.3-11.11 1.0-7.8 1.0-9.6<br>lisse-glatt-smooth |          |          | 2    |
| F16  | <b>76-104</b>                 | 16 | 22 | 55 | 5  | 16 | -        | 15° | 0.3-13.0  | 1.0-9.2  | 1.0-11.3 | 1    |
|      | <b>76-1076</b>                | 16 | 21 | 64 | 6  | 16 | -        | 16° | 0.3-13.0  | 1.0-9.2  | 1.0-11.3 | 1    |

Alésages standards (rond, carré, six-pans) selon liste de prix. Autres alésages sur demande.  
 Standardbohrungen (rund, vierkant, sechskant) gemäss Preisliste. Andere Bohrungen auf Anfrage.  
 Standard bores (round, square, hexagonal) according to price list. Other bores on request.

10) Article de base - Basisartikel - Basic item