


SCHAUBLIN **F** Page - Seite **17.1**

Pinces poussées - Druckspannzangen - Dead length collets



Obturbateurs pour pinces, voir page 70
 Dichtgummi für Spannzangen auf Seite 70
 Rubber seals for collets on page 70

Type	Art.	A	B	C	E	F	G	α	D min-max	Fig.
F4.5	76-76	4.5	6.75	17.25	1.8	4.5	-	15°		1
F6	76-599	6	10	30	3	6	-	15°	0.3-4.5	1
F7	76-66	7	10.7	26	2.9	7	-	15°	0.3-5.0	1
	76-206	7	10.5	26	3	7	-	15°	0.3-5.5	1
F8	76-577	8	12	42	4.5	8	-	16°	0.3-6.35	1
	76-1844	8	11	19	2	8	-	15°	0.3-6.5	1
	76-2024 10) 76-577	8	12	47.5	10	8	M6x0.5	16°	0.3-4.5	3
F10	76-86	10	15.5	47.5	5.5	10	-	20°	0.3-8.0 1.0-5.0 1.0-6.5	1
	76-1178	10	16	46	4	10	-	20°	0.3-7.0	1
	76-2021 10) 76-86	10	15.5	52	10	10	M8x0.5	20°	0.3-7.0 1.0-5.0 1.0-6.0 lisse-glatt-smooth	2
F12	76-78	12	18.1	44.5	4.3	12	-	15°	0.3-10.0 1.0-7.0 1.0-8.5 lisse-glatt-smooth	1
	76-578	12	18	64	6	12	-	16°	0.3-10.0 lisse-glatt-smooth	1

Alésages standards (rond, carré, six-pans) selon liste de prix. Autres alésages sur demande.
 Standardbohrungen (rund, vierkant, sechskant) gemäss Preisliste. Andere Bohrungen auf Anfrage.
 Standard bores (round, square, hexagonal) according to price list. Other bores on request.

10) Article de base - Basisartikel - Basic item