

Pinces poussées - Druckspannzangen - Dead length collets


| Type | Art. | A | B | C | E | F | G | α | D min-max | | | Fig. |
|-------|------------------------------|------|------|------|------|------|-------|----------|-----------|----------|-----------|------|
| | | | | | | | | | ○ | □ | ⬡ | |
| F22 | 76-71 | 22 | 30 | 55 | 6 | 21 | - | 15° | 0.5-17.0 | 1.0-12.0 | 1.0-14.5 | 1 |
| F23.8 | 76-2034 | 23.8 | 28.3 | 62 | 7 | 22 | - | 15°15' | 0.5-19.05 | 1.0-12.0 | 1.0-16.5 | 1 |
| F25 | 76-64 | 25 | 35 | 77 | 10 | 27 | - | 16° | 0.5-21.0 | 1.0-15.0 | 1.0-18.0 | 1 |
| | 76-2018 10) 76-64 | 25 | 35 | 85 | 18 | 27 | M22x1 | 16° | 0.5-20.0 | 1.0-14.0 | 1.0-17.0 | 2 |
| F26 | 76-90 26) | 26 | 32 | 67 | 7 | 27.5 | - | 13° | | | | 1 |
| F27 | 76-22 | 27 | 38 | 72.7 | 8 | 30 | - | 15° | 0.5-23.0 | 1.0-16.0 | 1.0-20.0 | 1 |
| | 76-2040 10) 76-22 | 27 | 38 | 83 | 18.3 | 30 | - | 15° | 0.5-23.0 | 1.0-15.5 | 1.0-19.05 | 4 |
| F28 | 76-93 | 28 | 38 | 70 | 7 | 28 | - | 15° | 0.5-23.0 | 1.0-16.0 | 1.0-20.0 | 1 |
| F30 | 76-63 | 30 | 42 | 80 | 10 | 34 | - | 16° | 0.5-26.0 | 1.0-18.0 | 1.0-22.22 | 1 |
| | 76-101 | 30 | 38 | 65 | 6 | 32 | - | 15° | 0.5-26.0 | 1.0-18.0 | 1.0-22.5 | 1 |
| | 76-2019 10) 76-101 | 30 | 38 | 79 | 20 | 32 | - | 15° | 0.5-25.4 | 1.0-18.0 | 1.0-22.0 | 3 |
| F32 | 76-221 | 32 | 45 | 75 | 8 | 34 | - | 15° | 1.0-27.0 | 2.0-19.0 | 2.0-23.0 | 1 |

Alésages standards (rond, carré, six-pans) selon liste de prix. Autres alésages sur demande.
 Standardbohrungen (rund, vierkant, sechskant) gemäss Preisliste. Andere Bohrungen auf Anfrage.
 Standard bores (round, square, hexagonal) according to price list. Other bores on request.

10) Article de base - Basisartikel - Basic item
 26) Sur demande - Auf Anfrage - On request