

**Pinces poussées - Druckspannzangen - Dead length collets**



**Obturbateurs pour pinces, voir page 70**  
**Dichtgummi für Spannzangen auf Seite 70**  
**Rubber seals for collets on page 70**

| Type | Art.                         | A   | B    | C     | E   | F   | G      | α   | D min-max |         |         | Fig. |
|------|------------------------------|-----|------|-------|-----|-----|--------|-----|-----------|---------|---------|------|
|      |                              |     |      |       |     |     |        |     | ○         | □       | ⬡       |      |
| F4.5 | <b>76-76</b>                 | 4.5 | 6.75 | 17.25 | 1.8 | 4.5 | -      | 15° | 0.3-4.0   |         |         | 1    |
| F6   | <b>76-599</b>                | 6   | 10   | 30    | 3   | 6   | -      | 15° | 0.3-4.5   |         |         | 1    |
| F7   | <b>76-66</b>                 | 7   | 10.7 | 26    | 2.9 | 7   | -      | 15° | 0.3-5.0   |         |         | 1    |
|      | <b>76-206</b>                | 7   | 10.5 | 26    | 3   | 7   | -      | 15° | 0.3-5.5   |         |         | 1    |
| F8   | <b>76-577</b>                | 8   | 12   | 42    | 4.5 | 8   | -      | 16° | 0.3-6.35  |         |         | 1    |
|      | <b>76-1844</b>               | 8   | 11   | 19    | 2   | 8   | -      | 15° | 0.3-6.5   |         |         | 1    |
|      | <b>76-2024</b><br>10) 76-577 | 8   | 12   | 47.5  | 10  | 8   | M6x0.5 | 16° | 0.3-4.5   |         |         | 3    |
| F10  | <b>76-86</b>                 | 10  | 15.5 | 47.5  | 5.5 | 10  | -      | 20° | 0.3-8.0   | 1.0-5.0 | 1.0-6.5 | 1    |
|      | <b>76-1178</b>               | 10  | 16   | 46    | 4   | 10  | -      | 20° | 0.3-7.0   |         |         | 1    |
|      | <b>76-2021</b><br>10) 76-86  | 10  | 15.5 | 52    | 10  | 10  | M8x0.5 | 20° | 0.3-7.0   | 1.0-5.0 | 1.0-6.0 | 2    |
| F12  | <b>76-78</b>                 | 12  | 18.1 | 44.5  | 4.3 | 12  | -      | 15° | 0.3-10.0  | 1.0-7.0 | 1.0-8.5 | 1    |
|      | <b>76-578</b>                | 12  | 18   | 64    | 6   | 12  | -      | 16° | 0.3-10.0  |         |         | 1    |

Alésages standards (rond, carré, six-pans) selon liste de prix. Autres alésages sur demande.  
 Standardbohrungen (rund, vierkant, sechskant) gemäss Preisliste. Andere Bohrungen auf Anfrage.  
 Standard bores (round, square, hexagonal) according to price list. Other bores on request.

10) Article de base - Basisartikel - Basic item