

Pinces tirées - Zugspannzangen - Pull-type collets



Alésage à cran
 Stufenbohrung
 Step bore

Obtrateurs pour pinces, voir page 70
 Dichtgummi für Spannzangen auf Seite 70
 Rubber seals for collets on page 70

Type	Art.	A	B	C	G	α	D min-max \bigcirc	L	Fig.
P4.5	78-153	4.5	6.75	22.9	M3.35	15°	0.30...2.50 2.51...3.00 3.01...4.00 4.01...4.50	- 8.5 4 3	1
P5	78-154	5	7	22.9	M3.5	15°	0.30...2.70 2.71...3.00 3.01...3.50 3.51...4.00 4.01...4.50 4.51...5.00	- 8.5 12 4 3 2	1
P6	78-150	6	8.5	27.2	M4	15°	0.30...3.20 3.21...4.50 4.51...5.00	- 11.5 4.5	1
	78-155	6	8.5	24.1	M4	20°	0.30...3.20 3.21...4.50 4.51...5.00	- 8.5 3.5	1
P9	78-157	9	13.2	39.3	M6	15°	0.30...4.70 4.71...7.00 7.01...8.00 8.01...9.00	- 24 7 5	1
P10	78-228	10	14	39	M7	15°	0.30...5.70	-	1
							5.71...8.00	21.5	
							8.01...8.50	6	
							8.51...9.00	5	
							9.01...9.50	4	
9.51...10.00	3								
P25	78-334	25	35	75	M22x1	16°	0.50...18.26	-	2
PR28	78-2013	28	32	73	-	8°	2.00...24.50	-	3
PR35.5	78-2012	35.5	40	80	-	8°	2.00...30.00	-	3
P36	78-2007	36	45	107	M33x1.25	16°	2.00...21.00	-	2

Alésages standards (rond, carré, six-pans) selon liste de prix. Autres alésages sur demande.
 Standardbohrungen (rund, vierkant, sechskant) gemäss Preisliste. Andere Bohrungen auf Anfrage.
 Standard bores (round, square, hexagonal) according to price list. Other bores on request.