

SCHAUBLIN
W

Page - Seite

22.1
Pinces tirées - Zugspannzangen - Pull-type collets

Fig. 1






Fig. 2



Alésage à cran
Stufenbohrung
Step bore



Obturbateurs pour pinces, voir page 70
Dichtgummi für Spannzangen auf Seite 70
Rubber seals for collets on page 70

Type	Art.	A	B	C	E	G	α	D min-max		L	Fig.
W10	80-1	10	14	43.6	-	$\emptyset 9.83 \times 0.833$	$\nless 45^\circ/5^\circ$	15°	0.30...6.70 6.71...8.00 8.01...8.50 8.51...9.00 9.01...9.50 9.51...10.00	- 15 6 5 4 3	1
	80-2009	10	14	49.5	8	$\emptyset 9.83 \times 0.833$	$\nless 45^\circ/5^\circ$	15°	0.30...6.35 6.36...8.00	- 21	2
W12	80-2	12	16	46	-	$\emptyset 11.75 \times 1.25$	$\nless 45^\circ/5^\circ$	15°	0.30...8.00 8.01...10.00 10.01...10.50 10.51...11.00 11.01...11.50 11.51...12.00 12.01...12.50	- 17 6 5 4 3 2	1
	80-93108 10) 80-2	12	16	52	8.8	$\emptyset 11.75 \times 1.25$	$\nless 45^\circ/5^\circ$	15°	0.30...8.00 8.01...10.00	- 24	2
W15	80-3	15	20.2	58.3	-	$\emptyset 14.75 \times 1.25$	$\nless 45^\circ/5^\circ$	15°	0.30...10.70 10.71...12.70 12.71...13.00 13.01...13.50 13.51...14.00 14.01...14.50 14.51...15.00 15.01...15.50 15.51...16.00	- 22 9.5 8.5 7.5 6.5 5.5 4.5 3.5	1
	80-93285 10) 80-3	15	20.2	67	12	$\emptyset 14.75 \times 1.25$	$\nless 45^\circ/5^\circ$	15°	0.30...10.20 10.21...12.70	- 32	2

Alésages standards (rond, carré, six-pans) selon liste de prix. Autres alésages sur demande.
Standardbohrungen (rund, vierkant, sechskant) gemäss Preisliste. Andere Bohrungen auf Anfrage.
Standard bores (round, square, hexagonal) according to price list. Other bores on request.

10) Article de base - Basisartikel - Basic item